

**LSA 40**

## **Low Voltage Alternator - 4 pole**

10 to 20 kVA - 50 Hz / 12.5 to 25 kVA - 60 Hz  
Electrical and mechanical data

**LEROY-SOMER**<sup>™</sup>

***Nidec***  
All for dreams

## Specially adapted to applications

The LSA 40 alternator is designed to be suitable for typical generator applications, such as: backup, marine applications, rental, telecommunications, etc.

## Compliant with international standards

The LSA 40 alternator conforms to the main international standards and regulations: IEC 60034, NEMA MG 1.32-33, ISO 8528-3, CSA C22.2 n°100-14, UL 1446 (UL 1004 on request), marine regulations, etc.

It can be integrated into a EC marked generator.

The LSA 40 is designed, manufactured and marketed in an ISO 9001 environment and ISO 14001.

## Top of the range electrical performance

- Class H insulation
- Standard 12-wire re-connectable winding, 2/3 pitch, type no. 6
- Voltage range:
  - 50 Hz: 220 V - 240 V and 380 V - 415 V (440 V)
  - 60 Hz: 208 V - 240 V and 380 V - 480 V
- High efficiency and motor starting capacity
- Other voltages are possible with optional adapted windings:
  - 50 Hz: 440 V (no. 7), 500 V (no. 9)
  - 60 Hz: 380 V and 416 V (no. 8), 600 V (no. 9)
- Complies with EN 61000-6-3, EN 61000-6-2, EN 55011, group 1 class B for European zone (EC marking)

## Excitation and regulation system suited to the application

Excitation system			Regulation options			
Voltage regulator	SHUNT	AREP (option)	C.T. Current transformer for paralleling	Mains paralleling	3-phase sensing	Remote voltage potentiometer
R220	Standard	-	-	-	-	-
D350	-	Standard	√*	√	√	√
D550	Option	Option	√*	√	√	√

√: Possible option      \* External mounting

## Protection system suited to the environment

- The LSA 40 is IP 23
- Standard winding protection for clean environments with relative humidity  $\leq 95\%$ , including indoor marine environments.
  - Options: - Filters on air inlet: derating 5%
  - Filters on air inlet and air outlet (IP 44): derating 10%
  - Winding protections for harsh environments and relative humidity greater than 95%
  - Space heaters
  - Thermal protection for stator windings
  - Steel terminal box

## Reinforced mechanical structure using finite element modelling

- Compact and rigid assembly to better withstand generator vibrations
- Two-bearing and single-bearing versions designed to be suitable for commercially-available heat engines
- Steel frame
- Aluminium flanges and shields
- Half-key balancing
- Sealed for life ball bearings
- Direction of rotation: clockwise and anti-clockwise (without derating)

## Accessible terminal box

- Easy access to the AVR and to the connections
- 8 way terminal block for reconnecting the voltage
- Predrilled holes for cable gland



# LSA 40 - 10 to 20 kVA - 50 Hz / 12.5 to 25 kVA - 60 Hz

## General characteristics

Insulation class	H	Excitation system	SHUNT	AREP
Winding pitch	2/3 (wind. 6)	AVR type	R220	D350
Number of wires	12	Voltage regulation (*)	± 1%	± 0.25%
Protection	IP 23	Short-circuit current	-	300% (3 IN): 10 s
Altitude	≤ 1000 m	Total Harmonic Distortion THD (**) in no-load	< 3%	
Overspeed	2250 R.P.M.	Total Harmonic Distortion THD (**) on linear load	< 5%	
Air flow	0.06 m <sup>3</sup> /s (50 Hz) - 0.072 m <sup>3</sup> /s (60 Hz)	Waveform: NEMA = TIF (**)	< 50	

(\*) Steady state (\*\*) Total harmonic distortion between phases, in no-load or on linear load






## Ratings 50 Hz - 1500 R.P.M.

kVA / kW - P.F. = 0.8																				
Duty/T°C	Continuous duty/40°C					Continuous duty/40°C					Stand-by/40°C					Stand-by/27°C				
Class/T°K	H/125°K					F/105°K					H/150°K					H/163°K				
Phase	3 ph.			1 ph.		3 ph.			1 ph.		3 ph.			1 ph.		3 ph.			1 ph.	
<b>Y</b>	380V	<b>400V</b>	415V	440V	ΔΔ	380V	<b>400V</b>	415V	440V	ΔΔ	380V	<b>400V</b>	415V	440V	ΔΔ	380V	<b>400V</b>	415V	440V	ΔΔ
Δ	220V	<b>230V</b>	240V		230V	220V	<b>230V</b>	240V		230V	220V	<b>230V</b>	240V		230V	220V	<b>230V</b>	240V		230V
<b>YY</b>	<b>200V</b>		220V			<b>200V</b>		220V			<b>200V</b>		220V			<b>200V</b>		220V		
<b>LSA 40 VS1</b> kVA	10	<b>10</b>	10	9	7	9	<b>9</b>	9	8	6.5	10.5	<b>10.5</b>	10.5	9.5	7.5	11	<b>11</b>	11	10	8
kW	8	<b>8</b>	8	7	5.5	7	<b>7</b>	7	6.5	5	8.5	<b>8.5</b>	8.5	7.5	6	9	<b>9</b>	9	8	6.5
<b>LSA 40 VS2</b> kVA	12.5	<b>12.5</b>	12.5	11	9	11.5	<b>11.5</b>	11.5	10	8	13.5	<b>13.5</b>	13.5	12	9.5	14	<b>14</b>	14	12.5	10
kW	10	<b>10</b>	10	9	7	9	<b>9</b>	9	8	6.5	11	<b>11</b>	11	9.5	7.5	11	<b>11</b>	11	10	8
<b>LSA 40 S3</b> kVA	15	<b>15</b>	15	13	10.5	14	<b>14</b>	14	12	10	16	<b>16</b>	16	14	11.5	16.5	<b>16.5</b>	16.5	15	12
kW	12	<b>12</b>	12	10.5	8.5	11	<b>11</b>	11	9.5	8	13	<b>13</b>	13	11	9	13	<b>13</b>	13	12	9.5
<b>LSA 40 S4</b> kVA	17.5	<b>17.5</b>	17.5	16	12.5	16	<b>16</b>	16	14.5	11.5	19	<b>19</b>	19	17	13.5	19.5	<b>19.5</b>	19.5	17.5	14
kW	14	<b>14</b>	14	13	10	13	<b>13</b>	13	11.5	9	15	<b>15</b>	15	13.5	11	15.5	<b>15.5</b>	15.5	14	11
<b>LSA 40 M5</b> kVA	20	<b>20</b>	20	18	14	18.5	<b>18.5</b>	18.5	16.5	13	21.5	<b>21.5</b>	21.5	19	15	22	<b>22</b>	22	20	15.5
kW	16	<b>16</b>	16	14.5	11	15	<b>15</b>	15	13	10.5	17	<b>17</b>	17	15	12	17.5	<b>17.5</b>	17.5	16	12.5

## Ratings 60 Hz - 1800 R.P.M.

kVA / kW - P.F. = 0.8																				
Duty/T°C	Continuous duty/40°C					Continuous duty/40°C					Stand-by/40°C					Stand-by/27°C				
Class/T°K	H/125°K					F/105°K					H/150°K					H/163°K				
Phase	3 ph.			1 ph.		3 ph.			1 ph.		3 ph.			1 ph.		3 ph.			1 ph.	
<b>Y</b>	380V	416V	440V	<b>480V</b>	ΔΔ	380V	416V	440V	<b>480V</b>	ΔΔ	380V	416V	440V	<b>480V</b>	ΔΔ	380V	416V	440V	<b>480V</b>	ΔΔ
Δ	220V	240V		240V		220V	240V		240V		220V	240V		240V		220V	240V		240V	
<b>YY</b>	208V		220V	<b>240V</b>		208V		220V	<b>240V</b>		208V		220V	<b>240V</b>		208V		220V	<b>240V</b>	
<b>LSA 40 VS1</b> kVA	10	11	11.5	<b>12.5</b>	9	9.5	10.5	10.5	<b>11.5</b>	8.5	11	11.5	12.5	<b>13.5</b>	9.5	11.5	12	13	<b>14</b>	10
kW	8	9	9	<b>10</b>	7	7.5	8.5	8.5	<b>9</b>	7	9	9	10	<b>11</b>	7.5	9	9.5	10.5	<b>11</b>	8
<b>LSA 40 VS2</b> kVA	12.5	13.5	14.5	<b>15.5</b>	11.5	11.5	12.5	13.5	<b>14.5</b>	10.5	13.5	14.5	15.5	<b>16.5</b>	12	14	15	16	<b>17</b>	12.5
kW	10	11	11.5	<b>12.5</b>	9	9	10	11	<b>11.5</b>	8.5	11	11.5	12.5	<b>13</b>	9.5	11	12	13	<b>13.5</b>	10
<b>LSA 40 S3</b> kVA	15	16.5	17.5	<b>19</b>	13	14	15.5	16.5	<b>17.5</b>	12	16	18	19	<b>20</b>	14	17	18.5	19.5	<b>21</b>	14.5
kW	12	13	14	<b>15</b>	10.5	11	12.5	13	<b>14</b>	9.5	13	14.5	15	<b>16</b>	11	13.5	15	15.5	<b>17</b>	11.5
<b>LSA 40 S4</b> kVA	17.5	19	20	<b>22</b>	14.5	16.5	18	19	<b>20.5</b>	13	19	20.5	21.5	<b>23.5</b>	15.5	19.5	21	22	<b>24.5</b>	16
kW	14	15	16	<b>17.5</b>	11.5	13	14.5	15	<b>16.5</b>	10.5	15	16.5	17	<b>19</b>	12.5	15.5	17	17.5	<b>19.5</b>	13
<b>LSA 40 M5</b> kVA	20	22	23	<b>25</b>	16	18.5	20.5	21.5	<b>23</b>	15	21.5	23.5	25	<b>27</b>	17	22	24.5	26	<b>27.5</b>	17.5
kW	16	17.5	18.5	<b>20</b>	13	15	16.5	17	<b>18.5</b>	12	17	19	20	<b>21.5</b>	13.5	17.5	19.5	21	<b>22</b>	14

**Efficiencies 400 V - 50 Hz (— P.F.: 0.8) (..... P.F.: 1)**






**Reactances (%). Time constants (ms) - Class H / 400 V**

	VS1	VS2	S3	S4	M5
<b>Kcc</b> Short-circuit ratio	0.7	0.67	0.6	0.6	0.61
<b>Xd</b> Direct-axis synchro. reactance unsaturated	167	174	190	195	193
<b>Xq</b> Quadrature-axis synchro. reactance unsaturated	85	88	97	99	98
<b>T'do</b> No-load transient time constant	719	790	837	878	926
<b>X'd</b> Direct-axis transient reactance saturated	17.2	16.3	16.8	16.4	15.4
<b>T'd</b> Short-circuit transient time constant	74	74	74	74	74
<b>X''d</b> Direct-axis subtransient reactance saturated	8.6	8.1	8.4	8.2	7.7
<b>T''d</b> Subtransient time constant	7	7	7.4	7	7
<b>X''q</b> Quadrature-axis subtransient reactance saturated	16.1	15.9	16.8	16.8	16.2
<b>Xo</b> Zero sequence reactance	0.71	0.68	0.7	0.68	0.64
<b>X2</b> Negative sequence reactance saturated	12.36	12.04	12.66	12.55	12.01
<b>Ta</b> Armature time constant	11	11	11	11	11

**Other class H / 400 V data**






<b>io (A)</b> No-load excitation current SHUNT / AREP	0.77 / 1.06	0.78 / 1.06	0.76 / 1.03	0.75 / 1.03	0.72 / 0.98
<b>ic (A)</b> On-load excitation current SHUNT / AREP	1.94 / 2.65	1.97 / 2.69	2.05 / 2.79	2.06 / 2.8	1.95 / 2.66
<b>uc (V)</b> On-load excitation voltage SHUNT / AREP	23.7 / 17.1	24 / 17.3	24.9 / 17.9	24.9 / 18	23.6 / 17
<b>ms</b> Response time ( $\Delta U = 20\%$ transient)	500	500	500	500	500
<b>kVA</b> Start ( $\Delta U = 20\%$ cont. or $\Delta U = 30\%$ trans.) SHUNT / AREP	24.6	29.9	36.1	43.3	52.7
<b>%</b> Transient $\Delta U$ (on-load 4/4) SHUNT / AREP - P.F.: 0.8 <sub>LAG</sub>	16.1	18.4	17.3	17.1	16.7
<b>W</b> No-load losses	461	514	540	590	645
<b>W</b> Heat dissipation	1597	1784	2063	2255	2352

Transient voltage variation 400V - 50 Hz



- 1) For a starting P.F. other than 0.6, the starting kVA must be multiplied by  $K = \text{Sine P.F.} / 0.8$
- 2) For voltages other than 400V (Y), 230V ( $\Delta$ ) at 50 Hz, then kVA must be multiplied by  $(400/U)^2$  or  $(230/U)^2$ .

**Efficiencies 480 V - 60 Hz (— P.F.: 0.8) (..... P.F.: 1)**






**Reactances (%). Time constants (ms) - Class H / 480 V**

	VS1	VS2	S3	S4	M5
<b>Kcc</b> Short-circuit ratio	0.67	0.65	0.57	0.57	0.58
<b>Xd</b> Direct-axis synchro. reactance unsaturated	174	180	201	204	201
<b>Xq</b> Quadrature-axis synchro. reactance unsaturated	88	91	102	104	102
<b>T'do</b> No-load transient time constant	719	790	837	878	926
<b>X'd</b> Direct-axis transient reactance saturated	17.9	16.8	17.8	17.2	16.1
<b>T'd</b> Short-circuit transient time constant	74	74	74	74	74
<b>X''d</b> Direct-axis subtransient reactance saturated	8.9	8.4	8.9	8.6	8
<b>T''d</b> Subtransient time constant	7	7	7.4	7	7
<b>X''q</b> Quadrature-axis subtransient reactance saturated	16.7	16.4	17.8	17.6	16.9
<b>Xo</b> Zero sequence reactance	0.74	0.7	0.74	0.71	0.67
<b>X2</b> Negative sequence reactance saturated	12.87	12.44	13.36	13.15	12.51
<b>Ta</b> Armature time constant	11	11	11	11	11

**Other class H / 480 V data**

<b>io (A)</b> No-load excitation current SHUNT / AREP	0.77 / 1.06	0.77 / 1.06	0.76 / 1.03	0.75 / 1.02	0.72 / 0.98
<b>ic (A)</b> On-load excitation current SHUNT / AREP	1.97 / 2.69	1.99 / 2.71	2.1 / 2.86	2.1 / 2.86	1.97 / 2.69
<b>uc (V)</b> On-load excitation voltage SHUNT / AREP	24.1 / 17.4	24.3 / 17.5	25.6 / 18.5	25.5 / 18.4	24 / 17.3
<b>ms</b> Response time ( $\Delta U = 20\%$ transient)	500	500	500	500	500
<b>kVA</b> Start ( $\Delta U = 20\%$ cont. or $\Delta U = 30\%$ trans.) SHUNT / AREP	29.4	35.8	43.3	51.9	63.1
<b>%</b> Transient $\Delta U$ (on-load 4/4) SHUNT / AREP - P.F.: 0.8 <sub>LAG</sub>	16.4	18.7	17.7	17.5	17
<b>W</b> No-load losses	643	717	755	825	904
<b>W</b> Heat dissipation	1866	2069	2447	2654	2763

Transient voltage variation 480V - 60 Hz




- 1) For a starting P.F. other than 0.6, the starting kVA must be multiplied by  $K = \text{Sine P.F.} / 0.8$
- 2) For voltages other than 480V (Y), 277V ( $\Delta$ ), 240V (YY) at 60 Hz, then kVA must be multiplied by  $(480/U)^2$  or  $(277/U)^2$  or  $(240/U)^2$ .

3-phase short-circuit curves at no load and rated speed (star connection Y)


LSA 40 VS1

Symmetrical —  
Asymmetrical - - -




LSA 40 VS2

Symmetrical —  
Asymmetrical - - -



LSA 40 S3

Symmetrical —  
Asymmetrical - - -



Influence due to connection

Curves shown are for star (Y) connection.


For other connections, use the following multiplication factors:

- Series delta : current value x 1.732 - Parallel star : current value x 2

3-phase short-circuit curves at no load and rated speed (star connection Y)


LSA 40 S4

Symmetrical —  
Asymmetrical - - -



LSA 40 M5


Symmetrical —  
Asymmetrical - - -



**Influence due to short-circuit**  
Curves are based on a three-phase short-circuit.  
For other types of short-circuit, use the following multiplication factors.

	3-phase	2-phase L/L	1-phase L/N
Instantaneous (max.)	1	0.87	1.3
Continuous	1	1.5	2.2
Maximum duration (AREP)		1.5	

Single bearing dimensions



Dimensions (mm) and weight				
Type	L maxi*	LB	Xg	Weight (kg)
LSA 40 VS1	469	407	186	73
LSA 40 VS2	469	407	196	80
LSA 40 S3	499	437	204	87
LSA 40 S4	499	437	221	92
LSA 40 M5	519	457	221	102

\* L maxi = LB + AH maxi + Z

Flange (mm)						
S.A.E.	P	N	M	XBG	β°	ω°
5	358	314.32	333.38	8	22°30'	45°
4	408	361.95	381	8*	15°	30°
3	460	409.58	428.62	8*	15°	30°


\* Four lateral holes removal on S.A.E. 3 and 4

Shaft height (mm)		
	Standard	Option
H	160	180
Feet length		
C	203	238
C1	25	22
A1	254	279
A2	230	243

Coupling			
Flange	3	4	5
Flex plate			
11 ½	x	-	-
10	x	x	-
8	x	x	-
7 ½	-	x	x
6 ½	-	x	x

Flex plate (mm)						
S.A.E.	BX	U	X	Y	AH	Z
11 ½	352.42	333.38	8	11	39.6	0
10	314.32	295.28	8	11	53.8	0
8	263.52	244.48	6	11	62	0
7 ½	241.3	222.25	8	9	30.2	6
6 ½	215.9	200.02	6	9	30.2	6


Torsional analysis data



Centre of gravity: Xr (mm), Rotor length: Lr (mm), Weight: M (kg), Moment of inertia: J (kgm²): (4J = MD²)																				
Flex plate	S.A.E. 6 ½				S.A.E. 7 ½				S.A.E. 8				S.A.E. 10				S.A.E. 11 ½			
	Type	Xr	Lr	M	J	Xr	Lr	M	J	Xr	Lr	M	J	Xr	Lr	M	J	Xr	Lr	M
LSA 40 VS1	211.7	428	25.54	0.0779	211.7	428	25.7	0.0802	243.5	428	26	0.0847	238.3	428	26.5	0.0964	221.1	428	27	0.1080
LSA 40 VS2	221.7	428	27.95	0.0867	221.7	428	28.11	0.0890	253.5	428	28.41	0.0935	248.3	428	28.91	0.1052	231.1	428	29.41	0.1168
LSA 40 S3	229.2	458	30.32	0.0936	229.2	458	30.48	0.0959	261	458	30.78	0.1004	255.8	458	31.28	0.1121	238.6	458	31.78	0.1237
LSA 40 S4	236.7	458	32.23	0.1004	236.7	458	32.39	0.1027	268.5	458	32.69	0.1072	263.3	458	33.19	0.1189	246.1	458	33.69	0.1305
LSA 40 M5	246.7	478	35.26	0.1102	246.7	478	35.42	0.1125	278.5	478	35.72	0.1170	273.3	478	36.22	0.1287	256.1	478	36.72	0.1403


NOTE : Dimensions are for information only and may be subject to modifications. Contractual 2D drawings can be downloaded from the Leroy-Somer site, 3D drawing files are available upon request. The torsional analysis of the transmission is imperative. All values are available upon request.

## Two bearing dimensions



Dimensions (mm) and weight				
Type	L	LB	Xg	Weight (kg)
LSA 40 VS1	507	425	198	82
LSA 40 VS2	507	425	208	89
LSA 40 S3	537	455	216	96
LSA 40 S4	537	455	233	101
LSA 40 M5	557	475	233	109

## Torsional analysis data



Centre of gravity: Xr (mm), Rotor length: Lr (mm), Weight: M (kg), Moment of inertia: J (kgm <sup>2</sup> ): (4J = MD <sup>2</sup> )				
Type	Xr	Lr	M	J
LSA 40 VS1	176.5	450.2	25.38	0.0731
LSA 40 VS2	186.5	450.2	27.79	0.0819
LSA 40 S3	194	480.2	30.16	0.0888
LSA 40 S4	201.5	480.2	32.07	0.0956
LSA 40 M5	211.5	500.2	35.10	0.1054

**NOTE :** Dimensions are for information only and may be subject to modifications. Contractual 2D drawings can be downloaded from the Leroy-Somer site, 3D drawing files are available upon request.  
The torsional analysis of the transmission is imperative. All values are available upon request.

**LEROY-SOMER**<sup>™</sup>

[www.leroy-somer.com/epg](http://www.leroy-somer.com/epg)

[Linkedin.com/company/leroy-somer](https://www.linkedin.com/company/leroy-somer)  
[Twitter.com/Leroy\\_Somer\\_en](https://twitter.com/Leroy_Somer_en)  
[Facebook.com/LeroySomer.Nidec.en](https://www.facebook.com/LeroySomer.Nidec.en)  
[YouTube.com/LeroySomerOfficiel](https://www.youtube.com/LeroySomerOfficiel)



***Nidec***  
**All for dreams**

© Nidec 2020. The information contained in this brochure is for guidance only and does not form part of any contract. The accuracy cannot be guaranteed as Nidec have an ongoing process of development and reserve the right to change the specification of their products without notice.

Moteurs Leroy-Somer SAS. Siège : Bd Marcellin Leroy, CS 10015, 16915 Angoulême Cedex 9, France.  
Capital social : 38 679 664 €, RCS Angoulême 338 567 258.